

NW 457 EcoX XSafe

Modular Ice Machine 216 kg

Item #:
Project:
Quantity:



FEATURES

- Vertical Cube System.
- T304 Stainless Steel Panels.
- Auto-alert Indicator Lights.
- Global standard footprint: strictly follows international imperial standards commonly adopted in the industry of reference.
- One touch cleaning: reduces labor costs and saves time and simplifies cleaning process.
- Front evaporator access: immediate access to the evaporating plate for quick self-maintenance operations.
- Stackable: add flexibility!
- Head only ice maker: requires a separate storage bin to collect the ice produced.
- XSafe: natural sanitation system, integrated inside the ice maker and operating automatically 24/7 to keep equipment clean & safe.

CONDENSING SYSTEM

Air cooled

RECOMMENDED BINS

Head	Bins		kg
NW 457	✓	SB393	181
	✓	SB530	243
	CBT48EAMCD CBT48FMCD	SB948	406

REFRIGERANT GAS

R290

VOLTAGE V/Hz/ph

230/50/1

LEGEND:

- ✓ : Perfect combination between ice maker and bin
- : Ice chute cut-out performed upon installation
- CBTxxxxxxxx : need additional bin top



NW 457
Dice 10 g
W 22 x D 22 x H 22 mm



NW H 457
Half Dice 6 g
W 10 x D 22 x H 28 mm

CERTIFICATIONS



OPERATING REQUIREMENTS

	Minimum	Maximum
Air temperature	10	40
Water temperature	5	35
Water pressure	1 bar (14 psi)	5 bar (70 psi)
Electrical voltage	-10%	+10%

IMPORTANT NOTICE:
Models and specifications are subject to change without notice.
This spec sheet is meant for commercial purpose only.
For technical documentation please refer to our service manuals.

www.scotsman-ice.it
www.scotsman-ice.com


Modular Ice Machine 216 kg

NW 457 EcoX XSafe

Modular Ice Machine 216 kg

Item #:
Project:
Quantity:

Modular Ice Machine 216 kg



UNIT DATA		SHIPPING DATA		(*) Data refer to 32°C Amb. / 21°C Water temperature conditions							
Size (W x D x H)	760 x 620 x 575 mm	Carton (W x D x H)	830 x 690 x 720 mm								
Net weight	73 kg	Weight	87 kg								
		24 h ice production kg °C Amb. / °C Water			Energy consumption (*)		Water usage (*)	Instant power	Compressor	Circuit wires	Max. fuse size
Version	Voltage	10°C/10°C	21°C/10°C	32°C/21°C	kWh/100 kg	kWh/24h	l/h	W	W	No. x Ømm²	A
NWH 457 AS	230/50/1	216	208	146	14.1	20.6	10.1	960	2941	3 x 1.5	16
NW 457 AS	230/50/1	216	204	157	12.8	20.1	11.5	960	2941	3 x 1.5	16